



Item	Parameter	LPM6060-50-30WW		LPM6060-50-30NW	
Product Photo					
		CCT: 3000K Ra:85		CCT: 4300K Ra:82	
Light Distribution					
Operating Current		1500mA	1700mA	1500mA	1700mA
Light Output	Lumens	3200 lm	3621 lm	3200 lm	3621 lm
	Illuminance at 2m	280 lux	369 lux	280 lux	369 lux
Electrical	Input current	Constant Current			
	Input Power	45W	55W	45W	55W
	Dimmer function	Optional			
Dimensions	Dimensions	592x592x45 mm.			
	Placement	Built-in in standard (60x60cm) ceiling or hanging from cable.			
Advised Drivers	PLN6036	Mean Well 800mA~1700mA driver. Non dimmable			
	ELN6048D	Mean Well 1400mA~1500mA driver. Dimmable with 0-10V.			
Luminaire	Weight	3500g (excluding weight of driver)			
	Efficiency	71 lm/W	66 lm/W	71 lm/W	66 lm/W
	Expected Lifetime	50,000 hours / 30.000 hours (B10 - L70 with Ta=25°C)			
Temperature	Ambient (°C)	0°C...30°C (Ta in free air)			
	Operation (°C)	0°C...60°C (Ta in free air)			
	Storage (°C)	0°C...70°C (Ta in free air)			
Luminaire Standard Compliance	CE	EN55015, EN61547, EN61000, EN60598-1			
	Eye Security	IEC62471			
	Energy Efficiency	ENERGY STAR® SSL			
	Protection Class	IP44			
	Environment	RoHS			